

SUB energy **WOOFER**

EBX F25.5 900W

ULTRA flat

VERIFIED WITH
KLIPPEL



Technical Specifications

Component	Passive Radiator	Reflex Sub Box
Woofers Size	mm (in.)	250 (10)
Passive Radiator Size	mm (in.)	300 (12)
Power handling W	peak	900
	cont. program	300
Impedance	Ω	4
Frequency response	Hz	38 ÷ 350
Sensitivity	dB/SPL	92
Magnet	High density flux ferrite	
Cone	Water repellent pressed paper	
Weight of one component	kg (lb.)	11,9 (26.24)

1. ULTRA Flat profile, keeping size to a minimum for ease of placement and hidden cosmetic integration within the vehicle.
2. Constructed from 18 mm MDF with internal bracing, minimizing enclosure losses.
3. Slanted lower panel helps to reduce back wave reflections and eases installation.
4. Low loss foam surround Passive Radiator, for powerful, undistorted output.
5. Low profile-high excursion subwoofer unit provides bursting dynamics.
6. Molded metal grille offers total speaker protection and great cosmetic appeal.
7. Reversible Hertz Logo, configurable to the different installation positions.
8. Proprietary connection terminals provide the utmost in functionality and safety.
9. Easy-Remove metal mounting system, for a clean and reliable installation.

MOUNTING ACCESSORIES

